

North American Datum 1983
Shaded relief and contour lines derived from the digital elevation model supplied by Natural Resources Canada. Illumination: azimuth 315°, altitude 45°, vertical exaggeration 1x.
Base map at the scale of 1:50,000 from Natural Resources Canada, with modifications.
Contour interval 10 metres. Elevations in metres above mean sea level.

ONE THOUSAND METRE GRID
UNIVERSAL TRANSVERSE MERCATOR GRID
ZONE 10 NORTH

GRID NORTH 1°01' WEST OF TRUE NORTH.
APPROXIMATE MEAN MAGNETIC DECLINATION 2021 FOR CENTRE OF MAP IS 17°07' EAST,
DECREASING ANNUALLY 13.2".

Disclaimer: while every effort has been taken to ensure the accuracy of the information on this map, the data was provided "as-is" without any warranty, guarantee, or representation of any kind. Whether expressed or implied, the Government of British Columbia does not accept any liability or responsibility for any loss or damage, whether direct or indirect, arising from the use of this map. This map is not intended for navigation purposes.

DRIFT THICKNESS (DT) CLASSIFICATION			
DT class	Description	Surficial geology map unit example*	Implications for exploration
1	Bedrock is the dominant unit exposed at surface.	R; R.Tv	Bedrock occurs at surface; optimal target for bedrock mapping and sampling programs.
2	Bedrock outcrops are common but not dominant, otherwise sediment cover is thin (<2 m).	Tv,R	Bedrock occurs at surface in less than half of drift thickness class 2 units. Bedrock mapping and sampling programs should target topographic highs where bedrock is most common. Bedrock may also be exposed in streams and meltwater channels where modern or glacial watercourses have eroded drift. Bedrock can typically be accessed in hand-dug pits on topographic highs where sediment cover is thin, but deeper excavations are required in concavities.
3	Bedrock is overlain by a continuous veneer (<2 m) of sediment with minor outcrop occurrences.	Tv	Bedrock may be exposed in streams and meltwater channels where modern or deglacial watercourses have eroded drift. Bedrock may be accessible in hand-dug pits on topographic highs where sediment cover is thin, but deeper excavations are required in concavities.
4	Bedrock is likely overlain by a continuous blanket (>2 m) of sediment.	GLv/Tb	Bedrock is unlikely to occur at surface; may be accessed with a small excavator on some topographic highs, but deeper excavations or drilling will be required in concavities. My be suitable for drill-supported till sampling where till does not occur at surface, or where profile sampling is desired.
5	Bedrock is likely overlain by thick depositional landforms and/or multiple stratigraphic sediment units.	GfC; GLb/Tb	Bedrock does not occur at surface. Minimum drift thicknesses of 5 m are expected. Deep excavations or drilling will be required to reach bedrock. Optimal locations for drill-supported till sampling where till does not occur at surface, or where profile sampling is desired.

*For full explanation of surficial geology classification see companion map publication "Surficial geology of the Pinchi Lake map area (NTS 093K/09), British Columbia, Geoscience BC map 2021-03-04c"

ONSITE SYMBOLS					
Bedrock outcrop
Till sample site
Mineral occurrence (see Table 1; numbers indicate Map ID)
Past Producer
Prospect
Developed Prospect
Showing
Park or protected area
Road ¹
Rail line
Stream ²
Definite
Intermittent or indefinite
<small>1. Roads displayed on map are from the Canvec 1:50k database (Natural Resources Canada) and do not include the extensive gravel forest service road network present in the area. 2. Classification provided by BC Freshwater Atlas.</small>					

Table 1. Mineral occurrences from MINFILE database (MINFILE, 2020). Letter and number designation under deposit type correspond to definitions provided by Lefebvre and Ray (1995) and Lefebvre and Hoy (1996).

Map ID	MINFILE No.	Name	Status	Commodity	Deposit Type
1	093K012	MURRAY RIDGE	Showing	Cr	M03: Podiform chromite
2	093K048	SUNSHINE	Showing	Hg	E01: Almaden Hg I08: Silica-Hg carbonate
3	093K047	CIN	Showing	Hg	E01: Almaden Hg I08: Silica-Hg carbonate
4	093K049	PINCHI LAKE MERCURY	Past Producer	Hg	E01: Almaden Hg I08: Silica-Hg carbonate
5	093K065	PINCHI LAKE	Showing	Magnetite	M07: Ultramafic-hosted talc-magnetite
6	093K079	DAD	Showing	Hg	
7	103J024	TSMIPSEAN PENINSULA	Showing	Kyanite	P02: Kyanite-sillimanite schists

Descriptive Notes

The mapping presented here is part of a series of surficial geology, till sampling suitability, and drift thickness maps completed for Geoscience BC's Central Interior Copper-Gold Research (CICGR): Surficial Exploration Project (See index map). The purpose of this map series is to inventory and characterize surficial materials and landforms to inform resource exploration (e.g., mineral, water and aggregate) and infrastructure development in British Columbia. The surficial geology interpretations follow standardized mapping protocols defined by the Geological Survey of Canada (Geldonde et al., 2016) and used by the British Columbia Geological Survey, ensuring accordance with existing and ongoing surficial geology mapping produced by the government. Polygons are delineated based on surficial material and morphology, and overlays are used to indicate geomorphological processes. Features such as bedrock outcrop or glaciofluvial landforms that are too small to delineate as polygons are identified using point and line symbols. The surficial geology was interpreted from 1.5 m resolution colour and near-infrared SPOT satellite imagery. Pseudo-stereo models were produced from the imagery using the Canadian Digital Elevation Model (Natural Resources Canada, 2013). The till sampling suitability mapping builds on earlier drift exploration potential maps developed by Proudfoot et al. (1995) and basal till potential mapping (e.g., Sacco et al., 2014; Ferby, 2014).

This map series was initiated to streamline the CICGR regional till geochemical and mineralogical sampling program. Subglacial till is ideal for assessing bedrock hosted mineral potential in areas covered by Quaternary sediments because it is commonly the first derivative of bedrock (Shills, 1993). It has a relatively simple and predictable transport history related to ice-flow directions, and geochemical and mineralogical anomalies in till are more extensive than in bedrock source (Leyson, 2001). This mapping focuses on identifying discrete occurrences of subglacial till to guide exploration programs. In central British Columbia, it is specifically important to distinguish subglacial till facies from ablation till facies, as ablation till has a more complex transport and depositional history and, therefore, is less suitable for mineral exploration.

Till sampling suitability is derived from the surficial geology interpretations. Each mapped polygon is attributed a suitability using a multi-class index that considers the proportions of surficial materials and geomorphological processes that have affected them. Suitability ratings are ultimately a function of the proportion of a polygon that contains in situ subglacial till that is suitable for sampling. This helps to inform the planning and execution of till sampling surveys by identifying areas where subglacial till can be readily sampled and areas where extra efforts or alternative sampling methods or materials may be required.


Drift thickness mapping provides an indication of the relative thickness of Quaternary sediment cover based on the results of the surficial geology interpretations. Drift thickness estimations consider the interpreted surface expression of map units (polygons) and the potential for preserved stratigraphic sequences. Stratigraphic sequences are assumed where depositional environments were non-erosional and pre-existing materials are likely preserved (e.g., beneath glacioclastic sediments and ablation till). The interpretations have not been calibrated with known depths to bedrock. Drift thickness maps can be used to inform bedrock mapping and prospecting programs because they identify areas where bedrock outcrops are likely present or where bedrock is overlain by shallow cover and may be accessed with hand tools. This mapping can also be used in combination with till sampling suitability to identify areas where drilling or trenching may be required to sample till, or provide information such as ice flow direction for drift-based exploration programs.

Acknowledgements

Funding for this project was provided by Geoscience BC. We thank Wayne Jackman at Noble Exploration Services Ltd. and his team for providing additional ground observations collected during the till sampling program.

Recommended citation

Johnson, C., Sacco, D.A., McGregor, C., Knox, C. 2021. Drift thickness of the Pinchi Lake map area (NTS 093K/09), British Columbia. Geoscience BC map 2021-03-04c, scale 1:50,000.



References

Geldonde, C., Cooley, R.B., Ken, D.E., Campbell, J.E., Eagles, S., Everett, D., Hovda, D.A., Hogg, E., Priest, M., Puchner, A., Roberts, L., Smith, H., and Westphalen, A. (2016). Surficial data model: the source language of the Integrated Geospatial Series of Canada data model for surficial geology maps (ed. ver. 2.3.14). Geological Survey of Canada, Open File 8236, 90 p.

Levy, M., 2014. Basal till potential of the Nechako River map area (NTS 093K/09), British Columbia. British Columbia Ministry of Energy and Mines, British Columbia Geological Survey Open File 1955-20, 12 p.

Holland, S.B., 1976. Landforms of British Columbia: a physiographic outline. British Columbia Ministry of Energy and Mines, and Petroleum Resources, British Columbia Geological Survey Bulletin 61, 188 p.

Lefebvre, D.V. and Hoy, T. (ed.), 1996. Selected British Columbia mineral deposit profiles. Volume 2: base metal deposits. British Columbia Ministry of Energy, Mines, and Petroleum Resources, British Columbia Geological Survey Open File 1996-10, 172 p.

Lefebvre, D.V. and Ray, G.E. (ed.), 1995. Selected British Columbia mineral deposit profiles. Volume 1: base metal deposits. British Columbia Ministry of Energy, Mines, and Petroleum Resources, British Columbia Geological Survey Open File 1995-10, 172 p.

Plafie, A., 2000. Surficial geology. Fort Fraser, British Columbia. Geological Survey of Canada, Map 1960A, scale 1:250,000.

Plafie, A., 1995. Geomorphology: inventory, interpretation and value gain context of 1:250,000 scale. Geological Survey of Canada, Open File 1995-10, 172 p.

Plafie, A. and Ballew, R., 1983. Regional till geochemical mapping: a new approach to understanding the distribution of glacial sediments. Canadian Journal of Earth Sciences, 20, p. 333-353.

Proudfoot, D.N., Bobrowsky, P.T., and Melnick, D.G., 1995. Drift exploration potential: a new approach to surficial geology maps. In: Goldworthy, P.T., Shanks, S., Nevel, J.M., and Marquardt, P.F. (eds.), Drift Exploration in the Canadian Cordillera. British Columbia Ministry of Energy and Mines, British Columbia Geological Survey Paper, 1995-2, p.23-31.

Shanks, S., 2014. Basal till potential of the Nechako River map area (NTS 093K/09), British Columbia. British Columbia Ministry of Energy and Mines, British Columbia Geological Survey Open File 2014-06-01, scale 1:50,000.

Shanks, S., 2014. Basal till potential of the Nechako River map area (NTS 093K/09), British Columbia. British Columbia Ministry of Energy and Mines, British Columbia Geological Survey Open File 2014-06-01, scale 1:50,000.

Index to Adjoining Maps of the National Topographic System

93 K/15 INZAN LAKE	93 K/16 TEZZERON CREEK	93 J/13 SALMON LAKE
93 K/10 STUART LAKE	93 K/9 PINCHI LAKE	93 J/12 CARRIER LAKE
93 K/7 SHASS MOUNTAIN	93 K/8 FORT ST. JAMES	93 J/5 BEAVER LAKE